

## CLAIMS:

1. A magnetic resonance imaging apparatus comprising:
- an acquiring device for exciting spins within a subject to acquire an  
5 imaging echo generated by the excited spins along with a navigator echo, with a  
reduced field-of-view via a plurality of receiver systems;
- the first correcting device for conducting phase correction on said imaging  
echo based on said navigator echo;
- the first image producing device for producing an intermediate image  
10 based on said phase-corrected imaging echo from each of said plurality of  
receiver systems;
- a generating device for generating a sensitivity matrix for said plurality of  
receiver systems;
- the second correcting device for phase-correcting matrix data in said  
15 sensitivity matrix; and
- the second image producing device for producing an image with a full  
field-of-view based on said intermediate image and said phase-corrected  
sensitivity matrix.
- 20 2. The magnetic resonance imaging apparatus of claim 1, wherein  
the reduction factor for said reduced field-of-view satisfies the following  
requirement:
- $$n \geq R > 1,$$
- where
- 25 R: the reduction factor, and  
n: the number of receiver systems.
3. The magnetic resonance imaging apparatus of claim 1, wherein  
said acquiring device implements said reduced field-of-view by  
30 enlargement of sampling intervals for a  $k$ -space.

4. The magnetic resonance imaging apparatus of claim 3, wherein said acquiring device implements said enlargement of the sampling intervals by enlargement of a step difference of phase encoding.

5

5. The magnetic resonance imaging apparatus of claim 1, wherein said plurality of receiver systems have respective receiving coils.

10

6. The magnetic resonance imaging apparatus of claim 5, wherein said receiving coils are surface coils.

15

7. The magnetic resonance imaging apparatus of claim 1, wherein said acquiring device employs an MS-DW-EPI technique in acquiring said imaging echo.

8. The magnetic resonance imaging apparatus of claim 1, wherein said acquiring device employs a technique other than the MS-DW-EPI technique in acquiring said imaging echo.

20

9. The magnetic resonance imaging apparatus of claim 1, wherein said generating device generates said sensitivity matrix based on a spatial distribution of reception sensitivity of said plurality of receiver systems with respect to the full field-of-view.

25

10. The magnetic resonance imaging apparatus of claim 9, wherein said generating device generates said sensitivity matrix after fitting the spatial distribution of the magnitude of the reception sensitivity of each of said plurality of receiver systems to a two-dimensional polynomial.

30

11. The magnetic resonance imaging apparatus of claim 10,

wherein

said generating device conducts said fitting by a method of least squares weighted depending upon the magnitude of the reception sensitivity.

5                   12. The magnetic resonance imaging apparatus of claim 11,  
wherein

a weight for said weighting is the square of the magnitude of the reception sensitivity.

10                   13. The magnetic resonance imaging apparatus of claim 10,  
wherein

said two-dimensional polynomial is a quadratic.

15                   14. The magnetic resonance imaging apparatus of claim 1, wherein  
said second correcting device homogenizes said phase.

15                   15. The magnetic resonance imaging apparatus of claim 1, wherein  
said second correcting device sets said phase to zero.

20                   16. The magnetic resonance imaging apparatus of claim 1, wherein  
said second correcting device sets said phase to a constant value other than  
zero.

25                   17. The magnetic resonance imaging apparatus of claim 1, wherein  
said second image producing device employs the following equation in  
producing said image:

$$\mathbf{V} = (\mathbf{S}^* \mathbf{S})^{-1} \mathbf{S}^* \mathbf{A},$$

where

**V:** pixel values of the image with the full FOV,

30                   **S:** a sensitivity matrix,

**S\***: an adjoint matrix of **S**, and

**A**: pixel values of the intermediate image.